


# IS-DG510P Series

10-ports DIN-Rail managed Layer 2/4 Industrial PoE Switch



The IS-DG510P Series full Gigabit managed 10-port Ethernet switch with up to 8 PoE IEEE 802.3af/at PoE ports provide easy to use plug-n-play applications; a full Gigabit network provides higher throughput than legacy Fast Ethernet network. The cost effective IS-DG510P Series managed switches can provide power and data directly through a single Ethernet cable, which is ideal for factory production line or embedded into machine system. The IS-DG510P Series managed switches are especially good for Building automation, CCTV, ITS and security/safety related applications.



## Key features

- ▶ Provide 8 Gigabit RJ45 Copper ports plus 2 100 / 1000 Based SFP(SX/LX/LHX) ports
- ▶ Support up to 8 PoE port, IEEE 802.3af/at PoE, 15.4/30 Watt output, Full Load
- ▶ Support up to 2 Ultra High Power PoE port, 60 Watt output Configurable
- ▶ Support Smart PoE management function, PoE On/Off, Scheduling.
- ▶ Support 9K Jumbo frames
- ▶ Layer 2 Line-Speed Switching Fabric, non-blocking
- ▶ Layer 4 ACL (Access Control List), QCL (QoS Control List), Port Control
- ▶ Network redundancy LACP, Spanning Tree Protocol, STP, RSTP, MSTP
- ▶ Support I.A. Ring, I.A. Chain (Network Load Balancing), 250pcs@20ms
- ▶ Support BLP (Bad Link Protection) of I.A. Ring
- ▶ Support Ring Coupling, Multiple Ring, Dual Homing
- ▶ Private/Port-based VLAN, IEEE 802.1Q Tag-based VLAN, Protocol-based VLAN, Private VLAN, IP-Subnet based VLAN, Voice VLAN, IEEE 802.1ad Double Tagging (QinQ), MVR, VCL
- ▶ Multicasting support IGMP v1/v2/v3, proxy & snooping, MLD snooping
- ▶ IEEE 802.1X Port-based access control / RADIUS / TACACS+ Server
- ▶ VeriPHY Cable Diagnostics, Per VLAN mirroring
- ▶ Redundant Power Input (46~57 VDC) & Reverse power protection
- ▶ SNMP v1/v2c/v3, Trap / Inform
- ▶ DIN-Rail Mount, Wall Mount installation
- ▶ Port Power Saving, Loop Protection, IP 30 Protection
- ▶ 2KV surge immunity on RJ45 Copper port, 1.5KV Hipot
- ▶ Fault Alarm Notification (Power, Ports)
- ▶ Support IPV4/V6

## Specification

### Ethernet

Operating Mode	Store and Forward, L2 wire-speed/non-blocking switching engine
MAC addresses	8K
Packet Buffer	4 Mbits
Jumbo frame	9K
Switching Fabric / Back Plane	20Gbps

### RJ45 Copper ports

Speed	10/100/1000 Mbps
MDI/MDIX Auto-crossover	Support straight or cross wired cables
Auto-negotiation/Duplex	10/100/1000 Mbps speed auto-negotiation; Full & Half Duplex

Ethernet Port Protection	1.5KV VRMS 1minute(Hipot), 2KV surge immunity on RJ45 Copper ports
PoE	IEEE 802.3af/at (15.4/30 Watt), PoE/PoE+, 60 Watt Ultra high power PoE

### Fiber Ports

Port Types supported	100/1000 Base SFP Slot
Fiber port connector	LC/RJ45 connector for fiber ports
Optimal fiber cable	Typical 50 or 62.5/125 $\mu$ m for multimode (mm) Typical 8 or 9/125 $\mu$ m for single mode (sm)

### Protocols & Standards

IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1D/w/s, IEEE 802.1Q/p, IEEE 802.1ab, IEEE 802.1X, IEEE 802.3ad LLDP, IPv4/IPv6, SNMP v1/v2c/v3, DHCP Option 82, BootP, TFTP, ARP, RARP, Telnet, Syslog, Flow Control, Back Pressure, ICMP, UPD, TCP
---

### Network Redundancy

I.A. Ring / I.A. Chain	Link Loss Recovery < 20ms@250pcs
Network Topology Optimize Functions	Ring Coupling, Multiple-Ring, Dual-Homing
Spanning Tree Protocol	IEEE 802.1D/1w/1s, STP/RSTP/MSTP
Port Trunk / LACP	Static Trunk or LACP (Link Aggregation Control Protocol)

### Bridge, VLANs, Protocols

Flow Control	IEEE 802.3x (Full Duplex) and Back-Pressure (Half Duplex)
Max VLANs	256
VLAN Types	Port-Based VLAN, Private VLAN, MAC-Based VLAN IEEE 802.1Q tag-based VLAN, IP Subnet-Based VLAN, Voice VLAN IEEE 802.1ad Double Tagging (QinQ), Protocol-Based VLAN, VCL
Multicast protocols	IGMP v1, v2, V3, up to 255 multicast groups IGMP snooping, querying, MLD Snooping, GVRP Immediate leave and leave proxy, Throttling and filtering
LLDP	IEEE 802.1ab LLDP / LLDP-MED

### Traffic management & QoS

Priority	IEEE 802.1p QoS, Ingress / Egress, QCL
Number of queues per port	8
Scheduling schemes	SPQ, WRR, SPQ+WRR
Traffic Shaper	Port-based shaping

### Security

Port Security	IP and MAC-based Access Control/Filter, Auth User / Privilege Level Control IEEE 802.1X Authentication Network Access Control / RADIUS / TACACS+ Server
Storm Control	Multicast / Broadcast / Flooding Storm Control / Port Access Control / Limiters

### Management

User Management Interfaces	Cisco-Like CLI (Command Line Interface) Web-based Management, Windows Utility for quick startup SNMP V1, V2c, V3 USM, RMON, Trap / Inform / Retry, Telnet (5 sessions)
Management Security	HTTPs, SSH, Access Management, Loop Protection RADIUS Client for Management
Upgrade & Restore	TFTP for Configuration Import / Export TFTP for Firmware Upgrade
Diagnostic	Syslog, Level Info / Warning / Error, Detailed Syslog Port Mirror, Per VLAN mirroring, CPU Load Monitor, Traffic Counter VeriPHY Ethernet Cable Diagnostics, ICMP Ping
PoE	Smart PoE management
MIBs	RFC 1757RMON 1, 2, 3, 9; RFC 2674 Q-Bridge MIB RFC 1213 MIB II; RFC 1493 Bridge MIB; RFC 2233 IF MIB
DHCP	Client Mode, Server Mode, Relay Mode, Snooping, Option 82
NTP/SNTP	YES
System Status	Device info/status; Ethernet port status

Green Ethernet	Port Power Savings
Layer 4 Security	Access Control List

## Power

Power Input	Redundant Power Input, Removable Terminal Block
Input Voltage Range	46-57 VDC
Reverse power protection	YES
Transient protection	> 15, 000 Watts peak
Power Consumption	17 Watt (Without PD Load), PSE: 8 x 30Watt, total power budget, 240 Watt

## Indicators

Power status indication	Power Input status
Ethernet port indication	Link & speed


## Environmental and Compliances

Operating Temperature	-40~75°C (Cold startup at -40°C)
Storage Temperature	-40~85°C
Humidity	5~95% (Non-Condensing)
Vibration, shock, free fall	IEC-60068-2-6, -27, -32
Certification Compliance	CE, FCC
Electrical safety	CE, UL 60950-1, CSA C22.2 No. 60950-1, EN 60950-1
EMC	FCC Part 15, CISPR 22 (EN55022) Class A IEC-61000-4-2, -3, -4, -5, -6 (Level 3)
RoHS & WEEE	RoHS (Pb free) and WEEE Compliant
MTBF	>25 years

## Mechanical

Protection	IP30
Dimension	154mm x 105mm x 108mm(LxWxD)
Weight	1.5 kg
Installation	DIN-Rail Mount, Wall mount
Relay Output	1A, 24V, Normal Open

## Dimension Diagram



## Ordering Information

Available Models	Description	10/100/1000Mb TX	100/1000Mb FX
IS-DG510P-2F-8	Industrial 10 port Gigabit Layer 2/4 Managed Switch, 8 PoE	8 (8 PoE)	2

## Accessories

1. 100 Mb SFP Modules
2. Gigabit SFP Modules
3. IS-RK2U 19" rack mount kit
4. IS-RK4U 19" rack mount kit

## Package Checklist

- IS-DG510P Switch
- Quick Installation Guide (Printed)
- Documentation & Software CD
- RS232 Console Cable
- RJ45/SFP Cap / Wall Mount kit / DIN-Rail kit