


KGEC-6310

Fanless Industrial Edge PC

with Intel® 8th Gen. CPU, 4x LAN, 4x USB, HDMI, DVI-D, 8-bit DIO



- Intel® Whiskey Lake-U 8th Gen. SoC
- 2x DDR4 2400 MHz SO-DIMM, up to 32GB
- 1x HDMI, 1x DVI-D
- 4x LAN, 2x USB3.1, 2x USB2.0, 2x COM, 8bit Digital I/O
- 1x M.2 2230 Key E
- 1x miniPCIe with SIM slot, support 4G LTE/WIFI/BT/CAN
- 1x mSATA, 1x 2.5" SATA3.0
- Support wall mounting and Din-Rail mounting
- 12~24V DC Wide Power supply



	Items	Descriptions
System	CPU	Intel® Whiskey Lake-U 8th Gen. SoC: Intel® Core™ i3-8145U (2.1GHz up to 3.9GHz, dual-core processor, TDP 15W), Intel® Core™ i5-8265U (1.6GHz up to 3.9GHz, quad-core processor, TDP 15W), Intel® Core™ i7-8565U (1.8GHz up to 4.6GHz, quad-core processor, TDP 15W), Intel® Celeron® 4305U (2.2 GHz, dual-core processor, TDP 15W)
	System Memory	2x 260-Pin SO-DIMM, dual channel DDR4 2133/2400 MHz, up to 32GB
	Expansion	1x full size miniPCIe (PCIe x1 & USB) with SIM slot, support 4G LTE/WIFI/BT/CAN module, 1x M.2 2230 Key E, with PCIe x1+USB2.0 signal, expansion of WIFI/BT module
	Graphics	Gen. 9th Intel® HD Graphics, HEVC/H265 HW HD en/decoder, DVI-D max resolution 2560x1600@60Hz, HDMI max resolution 4096x2304@60Hz, 2x independent display
	Audio	Realtek® ALC662 VD controller, Audio out and Mic high fidelity audio interface, support 5.1 channel
	LAN	3x Intel® I210AT PCIe Gb Ethernet, 1x Intel® I219LM PCIe Gb Ethernet, support iAMT12.0
	Storage	1x 2.5" SATA3.0 HDD / SSD, 1x mSATA full size support AHCI
	Digital IO	8 bit DIO (1x 10Pin phoenix)
	I-Port	Optional 1x LPT, USB2.0, 16bit DIO or miniPCIe and M.2 I/O ports (such as serial ports)
	I/O Ports	4x RJ45 Gb LAN 2x USB3.1 Type A, 2x USB2.0 Type A 8 bit DIO: 1x10pin phoenix 2x RS232/422/485 DB9 1x Audio out, 1x Mic 3.5mm phone jack 1x HDMI, 1x DVI-D
	LED	1x Power LED, 1x HDD LED, 3x CPU temperature control LED (Red is warning, Yellow is high, Green is normal)
	Control SW	1x Power button, 1x AT/ATX Select SW, 1x Clear CMOS Select SW
	Power Supply	DC 12~24V Input, 2x2-pin terminal connector, TDP: TBD
	Watchdog Timer	Watchdog timeout programmable via software 1 to 255 seconds
OS Support	Windows 10, Linux: Fedora, Ubuntu. RTOS: Intime, EC-Win, RTX-2014/2016, Ubuntu Preempt-RT	
Structure	Aluminum chassis, SGCC frame	
Mechanical	Color	Silk grey
	Mounting	Wall mounting, Din-Rail mounting
	Dimension (WxHxD)	202x151x81 mm
	Net weight	2,72kg
	Operating Temperature	-20°C ~ 60°C - wide operating temperature SSD
Environmental	Storage Temperature	-40°C ~ 85°C
	Storage Humidity	10~90%@40°C, non-condensing
	Vibration	5 grms/5~500Hz/random/in working (SSD); 1 grms/5~500Hz/random/in working (HDD)
	Shock	50g peak acceleration (11ms duration) (SSD); 20g peak acceleration (11ms duration) (HDD)
	EMC	CE / FCC Class B

All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. All brand or product names are trademarks or registered trademarks of their respective owners.

Ordering Information

Model No.	CPU	Descriptions
KGEC-6310/S001	Intel® Core™ i3-8145U	Industrial Edge PC, 2x DDR4 SO-DIMM, 4x LAN, 2x USB3.1, 2x USB2.0, 2x COM,8-bit DIO, 1x miniPCle, 1x M.2, 1x DVI-D, 1x HDMI, 1x mSATA, 1x 2.5" SATA3.0, DC 12~24V
KGEC-6310/S002	Intel® Core™ i5-8265U	Industrial Edge PC, 2x DDR4 SO-DIMM, 4x LAN, 2x USB3.1, 2x USB2.0, 2x COM,8-bit DIO, 1x miniPCle, 1x M.2, 1x DVI-D, 1x HDMI, 1x mSATA, 1x 2.5" SATA3.0, DC 12~24V
KGEC-6310/S003	Intel® Core™ i7-8565U	Industrial Edge PC, 2x DDR4 SO-DIMM, 4x LAN, 2x USB3.1, 2x USB2.0, 2x COM,8-bit DIO, 1x miniPCle, 1x M.2, 1x DVI-D, 1x HDMI, 1x mSATA, 1x 2.5" SATA3.0, DC 12~24V
KGEC-6310/S004	Intel® Celeron® 4305U	Industrial Edge PC, 2x DDR4 SO-DIMM, 4x LAN, 2x USB3.1, 2x USB2.0, 2x COM,8-bit DIO, 1x miniPCle, 1x M.2, 1x DVI-D, 1x HDMI, 1x mSATA, 1x 2.5" SATA3.0, DC 12~24V
PA-120DC19	AC/DC power adapter, DC 19V/6.32A 120W	

Dimensions

Unit: mm

